

Dystrybutor:

Mar Agency
ul. Nefrytowa 46
91-360 Łódź
NIP 947 110 05 62

DMUCHAWY MEMBRANOWE



DB40, DB60, DT60



DBMX80, 100, 120,
DT80



DBMX150
DBMX200



DBMX 250
DBMX 300

- Długa żywotność ✓
- Wytrzymała konstrukcja ✓
- Niskie zużycie energii ✓

Parametry dmuchaw

Model	DB40	DB60/DT60*	DBMX80, DT80*	DBMX100	DBMX120	DBMX150	DBMX200	DBMX250	DBMX300	
Ciśnienie pracy (mbar)	Przepływ (l/min) [zużycie energii W]									
0	70 [45]	102 [73]	143 [108]	152 [124]	175 [151]	255 [171]	276 [233]	462 [295]	489 [387]	
50	63 [45]	93 [71]	128 [105]	140 [122]	161 [148]	243 [168]	256 [221]	409 [284]	443 [379]	
100	54 [43]	80 [67]	113 [99]	128 [116]	147 [141]	217 [158]	236 [212]	356 [262]	397 [357]	
150	44 [40]	68 [63]	98 [91]	116 [109]	133 [132]	183 [145]	216 [201]	303 [233]	351 [329]	
200	34 [36]	57 [57]	83 [82]	100 [100]	120 [122]	150 [130]	200 [186]	250 [202]	300 [298]	
250	24 [31]	44 [52]	68 [71]	84 [90]	103 [111]	115 [112]	163 [169]	185 [167]	244 [262]	
Max ciśnienie	< 250 mbar									

Woltaż	230 V / 50 Hz								
Max.prąd (A)	0,41	0,59	0,63	0,82	0,94	1,2	1,75	1,80	2,60
Poziom hałas 1,5m (dB)	48	48	45	45	46	48	48	55	56
Waga (kg)	6,0	6,9	8,8	8,8	8,8	11,9	11,9	17,8	18,0
Wymiary D x S x H (mm)	226 x 178 x 206		262 x 216 x 228			294 x 226 x 247		375 x 231 x 219	
Złącze (Ø mm)	18		18			18		26	

*DT60 – niższe zużycie energii 102 [43]

*DT80 – niższe zużycie energii 143 [65]

